П	Do After			No Goats Racing
Н 0	H e	п e	e e	
t L	a	a	a t	Between Race Maintenance
a	t	t	u	
p a	# 1	# 2	r e	
$\Box$				Check tire temperatures with pyrometer ASAP when kart off track.
				Put engine at TDC.
				Plug exhaust with rubber stopper.
				Connect plug wire.
				Record tire temperatures on Setup Sheet.
				Record lap #, time, RPM, and temp on back of Setup Sheet.
				Analyze results.
				Check tire condition
				Clean tires with water. Check condition while cleaning.
				Dry tires with Scott towels.
				Prep tires when dry.
				Check and adjust pressure.
				Inspect drivetrain
				Check wheel lugs (7/16" deep socket, extension, ratchet)
				Check rear sprocket nuts (7/16" box end)
				Clean chain with brass brush
				Check chain tension (1/2")
				Check engine mounts (1/4" allen)
				Lube chain and wipe excess off sprocket and chassis
				Inspect air filter
				Rotate foam sock 90 degrees or change before feature race
				Check fuel level
				Wipe fill cap. Put cap in tray. Check level with flashlight.
				Fill to tank seam and tighten cap
				Change engine oil after hot laps + 1 heat
				Wipe dirt from fill plug and drain plug. Remove plugs and put in tray.
				Drain in clean pan and inspect oil
				Inspect magnetic drain plug and wipe clean
				Tighten drain plug firmly
				Measure 14 oz. oil and fill. Tighten fill plug firmly.
				Make necessary chassis and tire changes